## DEVELOPMENT STANDARDS FOR RC ZONE

ZONE	DC I
ZONE	RC
(Standard method of Development)	Rural Cluster.
AREA REQUIREMENT	5 acre minimum for each dwelling with its
	accessory buildings.1
MAXIMUM COVERAGE	10% including accessory buildings.
MINIMUM FRONT YARD SETBACK	50 ft.
MINIMUM SIDE YARD SETBACK	Total 40 ft.
THE SECTION OF THE SECTION	One side 20 ft.
	50 ft. from lot abutting public street. <sup>2</sup>
MINIMUM REAR YARD SETBACK	35 ft.
MINIMOWI KEAR TARD SETDACK	00 11.
MINIMUM LOT FRONTAGE	300 ft. at front building line.
MINIMUM LUT FKUNTAGE	300 ft. at street line.
	טטט זו. מו אוופנו וווופ.
	50 ft.
MAXIMUM BUILDING HEIGHT	OU II.
A COPEGGODY PLIN PANGE	Description of the second order
ACCESSORY BUILDINGS	Rear yard only.
	Occupy no more than 25% of rear yard.
	80 ft. from front line.
	15 ft. from side line.
	10 ft. from rear line.
	50 ft. from lot abutting public street. 2
	50 ft. max. height.
REMARKS	<sup>1</sup> Not applicable if lot recorded by plat or deed
	prior to classification in RC zone. Area
	requirements not applicable.
	<sup>2</sup> This setback must consist of any scenic
	setback indicated on an approved and adopted
	master plan or 50 ft., whichever is greater.
	, , , , , , , , , , , , , , , , , , , ,